

4375 WIDE BELT SANDER

"My Safety Speed Wide Belt Sander has cut our sanding time down 70% and does such a great job our hand sanding is almost eliminated."

—Joseph Brown, Joseph Brown Woodworking and Cabinets, Langlois, OR

With heavier construction than the 3760 the 4375 sanders are ready to go to work in your busy shop environment. The larger 75" belt has 25% more abrasive surface than the smaller 60" belt machines. The larger belt translates to increased capacity, less heat accumulation, less maintenance and fewer belt replacements. With a fully adjustable platen these sanders will deliver a perfect smooth finish every time.



SPECIFICATIONS

Main Motor	10 Hp, 1~220V,	20 Hp, 3~208/230/460V,
Options	50/60Hz, 41 amps	50/60Hz, 54/50/25 amps
Max. Working Width	42"/1070mm	
Max. Working Length	Unlimited	
Min. Working Length	12"/305mm	
Max. Working Thickness	7 1/4"/184mm	
Min. Working Thickness	1/8"/3mm	
Vacuum Requirement	1000 CFM	
Conveyor speed	0-18 fpm	
Durometer of Contact Roller	60	
Sanding Belt Size	43" x 75"	
Shipping Weight (approx.)	2187 lbs/992 kg	

✓Optional Equipment shown on machine.

OPTIONAL EQUIPMENT

- 30 Hp, 3~, 208/230/460V*, 50/60Hz, 83/75/37.5 amps
 - ✓Hour meter.
 - ✓Digital readout.
 - ✓Power lift table.
 - Sanding belts.
- *additional parts needed for 460V operation.

STANDARD EQUIPMENT

- Photo electric belt tracking.
- Pneumatic belt tensioning.
- 2 1/2" graphite covered felt pad and adjustable platen.
- 2 rubber-covered pinch rollers 2 1/2" OD.
- 2 machined idler rollers 4 1/4" OD with 1" bearings.
- Rubber-covered contact roller 5 1/4" OD with 1 5/8" drive bearing.
- Conveyor table set on four 1" acme thread jackscrews.
- 2 height adjustment indicators.
- 6" internal dust chute.
- 4 emergency stops.
- 3 year warranty.