



Tape Advance



Accutrim System



Glue Pot

Operators looking for more flexibility and capacity should consider the 72GP Glue Pot Edgebander. This dependable glue pot machine with adjustable glue extrusion performs similar to other units costing thousands of dollars more. The price and performance of this machine makes it the perfect choice for the small to medium sized woodworking shop.

FEATURES & BENEFITS

- Digital P.I.D. temperature control to reduce glue overheating and burning with standby temperature mode.
- Micro adjust tape guide makes changing tape widths fast and simple.
- Electromagnetic end cutters means no need for compressed air supply.
- Dust collection outlet keeps trimmings off your workpiece and the floor.
- Easy to set-up, operate, and maintain.
- Small footprint.
- Anodized glue pot interior for ease of cleaning.
- Built in safety control to prevent glue spindle motor from being turned on before glue is melted.
- Short 10-12 minute glue heat up time.
- Sealed ball bearing rotary movement.
- Accutrim edge trim system uses industrial duty trim router motors to ensure quality finish.
- Automatic conveyor for consistent feed rate.
- Solid edge flush trimming and edge molding capability.
- Machined billet aluminum components.
- American made with 3 year warranty.

SPECIFICATIONS	
Dimensions (shop)	72" L x 48" H x 37" D
Shipping Weight	540 lbs/245 kg
Power Supply	220V, 20 amps, 1~
Tape Types	Polyester / PVC / Wood Single Laminate Strips
Tape Widths	1/2"/13mm to 1 3/4"/45mm
Min. Panel Length	6"
Min. Panel Width	3 1/2"
Max Thickness	1 mm
Max Feed Rate	24 FPM